

WING 2

ANCHOR POINT

A4
AISI 316

EN
795 - A



UNOBTRUSIVE

Very compact device that provides an anchorage point for an operator.

PRACTICAL

With its light weight, it is ideal as an anchor point for the safety rope during suspension work.



CODES AND DIMENSIONS

CODE	material	weight [g]	anchor system diameter*	pcs
WING2	stainless steel AISI 316	44	M12	1

* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

MOBILE

MOBILE ANCHOR POINT

EN
795 - B

CE



REMOVABLE

It can be assembled and disassembled easily and quickly, to safely ensure temporary access to the roofing.

FUNCTIONAL

It can be temporarily installed on doors, windows and inclined skylights, with no structural damage.



CODES AND DIMENSIONS

CODE	material	L [mm]	B [mm]	H [mm]	weight [kg]	pcs
MOBILE	EE30 aluminium	1450	770	175	6,7	1

The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

